



1.4 m dish made of impact resistant ABS.

SMW OA-1400 is a satellite dish designed for reception of low and medium power satellites in fringe areas. It's also excellent for use in SMATV. The dish diameter is 140 cm and it is supplied either with a fixed mast mount, or polar mount for motorized systems.

OA-1400 meets SMW's high standard of quality. The dish is made of ABS, which is a light and impact resistant material. Compared to aluminium dishes, they can withstand rough handling during transportation and installation. Due to the vaccuum shaping technique used in the manufacturing process, a high surface accuracy is repeatedly obtained and therefore all dishes are exactly alike. The dish is coated with EMC Ni-layer covered by an Acrylic topcoat, and the back of the dish is covered by a UV-resistant layer.

An offset angle of 13° and the short focal distance like a prime focus dish makes a very compact design. The discrete grey colour blends in well with its surroundings.

Our manufacturing quality ensures all dishes have both high efficiency and gain and all production take place in our dish manufacturing plant in Motala.

The OA-1400 is very easy to assemble and install. All parts are in one box and even your choice of SMW LNB could be included to make a complete outdoor unit.

A comprehensive assembly and installation guide ensures trouble-free installation.

All this puts the SMW OA-1400 into the very top range of satellite dishes, with excellent performance and reliability.



Specification **SMW OA-1400**

Satellite dish

OA-1400

Size Type

1500 x 1420 mm Offset 13°

Material dish

5.5 mm ABS

Material back support Surface accuracy

Steel ring 0.5 mm RMS

Finish, dish

EMC Shielding coat +

Galvanized + back support

Acrylic top coat

Polyester powder coat

Frequency range Gain @ 11.3 GHz 10.7-12.75 GHz 42.8 dB

f/D ratio

0.45

Beam width 11.3 GHz Edge illumination

1.2° -10 dB

Weight

16.2 kg

Fixed Mount

Mast mount 50-76 mm

Type Material Finish

Steel

Galvanized +

Polyester powder coat

Elevation Weight

0-55° 6.1 kg

Polar Mount 1400

Material

Steel

Finish

Galvanized +

Satellite range

Polyester powder coat 137° (57° West to 80° East) with an 400 mm actuator.

90° with an 300 mm actuator.

Mast dimension

Weight

7.0 kg

Accessories

Low Noise Converters

SMW DUO Focal

SMW LNB SMW XLNB

50-76 mm

SMW TWIN

Polarizers Feed horns SMW XF-45 SMW XM-140

SMW XM-144 V/H

Packing

Size Weight 152 x 144 x 28 cm 22.3 kg (Fixed mount) 23.2 kg (Polar Mount)







Distributor: